



### DIMENSIONS

100L x 160H x 30W (mm)

### FEATURES

1. 8 sets of door opening passwords which can be set by user.
2. Water-proof, anti-magnetic, no battery required, long durability.
3. Registration or deletion on a certain card capacity.
4. 2,000pcs. card capacity, 8-digit card number.
5. Audio tone indicator, stainless steel keypad(2X6)
6. Polycarbonate fireproof material for casing (white or dark-gray).

### SPECIFICATIONS

- Standard model machine.
- 16X2 STN LCD back-light display, 4 LED indicators, 2 photocouplers input points, 3 output points.
- Five door opening methods: Password door opening, proximity card door opening, proximity card plus password opening, both password or proximity card door opening and specific system password door opening.
- Door opening time duration from 1-99 seconds.
- 8 sets of door opening password which can be set by users.
- Duress code installation. If user is being held as hostage specific password can be entered and help signal will be dispatched immediately.

- If card is not being applied or encountered illegal entry, alarm will be activated.
- Single card proximity registration, single card number entering or whole batch entering.
- Registration or deletion on a certain card capacity.
- Tamper switch. Alarm will be activated when machine is being tampered with force.
- 2,000pcs. card capacity, 8-digit card number.(ST-660:10,000 pcs card capacity)
- Read range: 10~25cm (depending on the card model).
- 2X6 stainless steel durable buttons, anti-acidity and salinity.
- Polycarbonate fire-proof material for casing, thickness: 3mm, white or dark gray.
- Fixing of upper and lower covers are by special designed screws and requiring special tool to assemble and dismantle.
- Power consumption: 1.8W, power supply: DC12v/1A.
- Application of frequency:125KHz.
- Dimensions of outer case: 10LX16HX3W(cm), weight:350g.
- Operating temperature: 0°C~55°C. Humidity 85% Rh max.

**PT. Citra Amantosa Sejati.** Kebon Jeruk Baru, Ruko blok A-15, Jakarta 11530

Phone : 021-5308435, 5323403, 5350058 Fax. : 021-5308434

E-mail : [info@cas.co.id](mailto:info@cas.co.id) Web-site : <http://www.cas.co.id>