

Electric Deadbolts

SD-997A - For Fail Secure
 SD-997B - For Fail Safe
 SD-997B-24 (for 24VDC Fail Safe applications)
 SD-997SMB - Surface Mount Bracket

Features

SD-997A- Fail Secure:

- ◆ Add concealed deadbolt security to most wood or hollow metal doors with the added convenience of electrical operation.
- ◆ Fail-Secure application (locks if power is lost)
- ◆ Incorporates manual lock/unlock cylinder to operate the SD-997A if power is lost (turn lock knob from inside protected premises and/ or use key from outside protected premises.
- ◆ Door open/close monitor (NO/C/NC)
- ◆ Adjustable door lock delay timer (0, 3, 5 or 9 seconds)
- ◆ Control wire allows releases without cutting units power.
- ◆ Magnetic switch determines door position for positive locking.
- ◆ Solenoid shuts off if door not closed properly to prevent burning out.
- ◆ Use with an optional digital keypad for high security without a key.
- ◆ Easily connects to SECO-LARM's SK-983A Electronic Keypad.
- ◆ Over current protection 1.5A
- ◆ Include all necessary hardware.

SD-997B Fail-Safe


- ◆ Similar to SD-997 but for Fail-Safe operation (also does not include locking cylinder or second wire connector)

SD-997SMB

- ◆ This new electric deadbolt mounting bracket kit allows you to mount SECO-LARM's SD-997B deadbolt on the door jamb instead of in the door and door frame for those situation where in-door mounting is not possible due to space or door material.
- ◆ SD-997SMB kit includes two brackets, one for the deadbolt itself, and the other for the deadbolt's strike plate. One side of the brackets can be quickly removed for easy screwing into the door or the door jamb. Installation on nearly any type of door is fast and easy.
- ◆ The brackets have an attractive brushed aluminum finish, and were designed to withstand years of continuous locking and unlocking.

SD-997UB U-Bracket

- ◆ Use with SD-997B only.
- ◆ For surface mount on the door jamb.
- ◆ Two brackets included.
- ◆ Attractive brushed aluminum finish
- ◆ Use U-Brackets for frameless glass door.



Specifications:

	SD-997A	SD-997B	SD-997B-24
Operation	Fail-Secure	Fail-Safe	Fail-Safe
Current Draw	Standby:320mA Activated:880mA	Standby:360mA Activated:900mA	Standby:170mA Activated:420mA
Status Sensor	SPDT, 500mA @ 12VDC (N.O./C./N.C.)		SPDT, 250mA @ 24VDC (N.O./C./N.C.)
Operation Voltage	12VDC	12VDC	24VDC
Adjustable Delay Timer	0,3,5,9 sec.s	0,2,5,5,9 sec.s	0,2,5,5,9 sec.s
Weight (approx.)	2lbs., 5oz (1kg)	1lb.,13oz. (0.82kg.)	1lb.,13oz. (0.82kg.)